

With any air conditioning system the key result we are looking to achieve is comfort. We want to be comfortably cool during the heat of summer and comfortably warm in the depths of winter.

The YORK® range of High Static Ducted Air Conditioning units had been designed specifically with comfort in mind. They are also designed to provide this comfort in an easy to operate and highly efficient unit.

The wide range of sizes can accommodate most customer needs and their flexible installation makes them an easy fit for a variety of applications.

All models meet the highest energy efficiency ratings, so less energy is consumed without sacrificing the comfort. Both the condensing units and indoor units are engineered for quiet operation.



Specifications

Model	Indoor Unit	Outdoor Unit	6850018	6850038	6850048	6850054	6850074
			6850016	6850036	6850046	6850052	6850072
Indoor Unit							
Power Supply	V-ph-Hz		240-1-50	240-1-50	240-1-50	415-3-50	415-3-50
Mode			Inverter				
Cooling	Rated Capacity	kW	10.5	14	17	20	26
Heating	Rated Capacity	kW	10.5	14.5	17.5	20	26.4
Cooling	Rated Input	kW	3.18	4.24	5.15	6.2	8.2
Heating	Rated Input	kW	3.2	4.39	5.30	6.2	7.83
	AEER	W/W	3.1	3.1	3.1	3.11	3.11
	ACOP	W/W	3.1	3.1	3.1	3.11	3.29
	Airflow H/M/L	L/sec	584/486/389	889/708/522	1056/847/639	1289/1159/1037	1289/1159/1037
	Unit Dimensions	WxDxH	1200x625x380	1200x625x380	1400x858x440	1470x795x510	1470x795x510
Starter sizes	Supply	mm	1000x253	1000x253	1188x385	800x200	800x200
	Return	mm	1145x334	1145x334	1188x385	1138x390	1138x390
Outdoor unit							
Power Supply	V-ph-Hz		240-1-50	240-1-50	240-1-50	415-3-50	415-3-50
Running Current	Amps		21	26	26.5	20	20.5
Compressor			Rotary	Rotary	Rotary	Scroll	Scroll
Sound Pressure Level	dB(a)		62.9	64	63.7	66	66
Sound Power Level	dB(a)		68.9	71.3	70.6	73	73
Refrigerant			R410A	R410A	R410A	R410A	R410A
Refrigerant charge length	Metres		5	5	5	5	5
Refrigerant Pipe Sizes (Suc/Liq)	Dia. mm		9.52/15.9 (3/8"-5/8")	9.52/19.05 (3/8"-3/4")	9.52/19.05 (3/8"-3/4")	12.7/28.6 (1/2"-1 1/8")	12.7/28.6 (1/2"-1 1/8")
Max pipe length	Metres		65	65	65	50	50
Max difference in level	Metres		30	30	30	30	30
Unit Dimensions	WxDxH		946x410x810	952x410x1333	1221x694x1013	948x968x1585	948x982x1585
Operating range	°C		-15 to 50	-15 to 50	-15 to 50	-15 to 48	-15 to 48



INSTALL CONFIDENCE

Your nearest Bonaire stockist is:-



York® air conditioning units come standard with a five year warranty when used in domestic applications. Commercial applications warranty is one year.



The leaders in heating and cooling

For further information please phone:

VIC (03) 8795 2424

SA (08) 8307 5300

WA (08) 9454 1010

Dubbo (02) 6882 2733

Leeton (02) 6953 6444

bonaire.com.au

A CLIMATE TECHNOLOGIES BRAND ABN 13 001 418 042.
26 Nylex Avenue, Salisbury 5108.

In the interest of continued product improvement, Bonaire reserves the right to alter specifications without notice E. & O.E. Colours represented are as accurate as the printing process will allow. Images used, are for illustration purposes only.



**Ducted Inverter
Reverse Cycle Systems**



Proudly distributed in Australia by the Bonaire Specialist Dealer network



YORK®

Delivering healthier environments and sustainable solutions throughout the world.

York was one of the industry pioneers developing the first forms of air conditioning in the late 1800's. For over 135 years the York brand has been building a reputation quality and reliability. They are now renowned for manufacturing an extensive range of commercial products which have been used to cool and heat some of the most famous structures throughout the world including the Empire State Building, the US Capital Building, the English Chunnel and the Sydney Opera House. The same commercial unit build quality and robustness has been extended to their residential product resulting in York being well recognised as a premium product supplying air conditioning systems to American households in the millions.

York has also been a long serving member of the Energy Star® program in the United States which over the years has led to savings of over US\$17 billion on energy bills and significantly contributed to reducing greenhouse gas emissions.

In 2006, York became a brand of Johnson Controls, a company that is a world leader in building efficiency. Using the renowned resources of the Johnson Control business, York continue to devote significant effort into building products with reliability and features that customers desire. The York commitment extends to the performance and reliability testing of their product which is unmatched the air conditioning industry.

Bonaire®

The Leaders in heating and cooling

For over 60 years Bonaire has been providing heating and cooling solutions for Australians and in many parts of the world. As one of the early pioneers of heating and cooling in Australia, Bonaire has been responsible for researching the latest technologies and developing these technologies into air conditioning products which are the forefront of airconditioning.

Our engineering team comprise some of the most experienced people in the air conditioning industry in Australia who are continually striving to refine and improve the products to ensure the optimum in quality and reliability.

Bonaire boasts a range of products which include proven high performing yet economical to run domestic and commercial evaporative coolers as well as mid to high efficiency, fully featured ducted gas heaters.

Bonaire products have been designed to provide effective and efficient heating and cooling for the harshest of Australian environments. The quality, durability and reliability is now recognised around the world resulting in many of the products being sold in many countries outside of Australia.

Bonaire is a part of the Climate Technologies group, a privately owned wholly Australian company with manufacturing plants in Adelaide, South Australia and Leeton, New South Wales.

YORK and Bonaire.

Two great names, one great partnership

YORK has appointed Bonaire as the Australian distributor. So now Bonaire can bring to you and your family world class, user friendly cooling and heating products right here in Australia.

Whether you are looking to condition a small area with a wall split, a ducted reverse cycle system or looking for the optimum in luxury with a combined gas heating /refrigerated cooling dual cycle system, Bonaire and York have the perfect system for you.



Indoor unit

- Slim Design
- Easy installation
- Excellent performance
- Easy maintenance
- Wireless controller (optional)
- Multi-zone control (optional)
- Auto Random Restart
- Long Duct Connection

Outdoor Condensing unit

- Compact size
- More sturdy and durable
- High Efficiency compressor
- Low noise
- 3-minute protection
- Valve protection
- Easier installation
- Easier maintenance
- Universal design



Remote Control

- Mode: Auto-Cool-Dry-Heat-Fan
- Fan speed: Auto-Low-Med-High
- Timer ON/OFF
- Temp setting
- Weekly Timer
- Follow me
- Child Lock
- LCD Display
- Clock

An efficient solution for more comfortable environments

Features and Benefits



24-Hour Timer

Allows programmed start times up to 24 hours in advance for flexible and more convenient operation.



Weekly Timer

Optional weekly timer allows for customised programming of on/off times each day of the week for more flexible and convenient operation.



R410-A

Environmentally-friendly refrigerant cools and heats more efficiently without destroying the ozone layer.



Self Diagnosis

Clearly displayed failure codes allow for quicker troubleshooting and easier maintenance.



Compact Design

Smaller dimensions for easy installation, transportation and reduced cost.



3-Minute Protection

A 3-minute delay before the compressor will restart helps avoid compressor damage and work time.



Auto Restart

Unit is automatically returned to previous operating conditions after a power outage for simplified operation.



Multi-Speed Fan

Multi-speed fan helps satisfy various airflow requirements.

Inner Groove Copper Tubes

Inner groove copper tubing allows more refrigerant to pass through improving heat exchange by 30 to 50% when compared to traditional copper tubing and lowering power consumption while keeping output capacity at the same level.



Follow Me

A temperature sensor embedded in the remote control helps ensure accurate air temperature around the user and not just around the indoor unit, providing maximum comfort.

